

SM-5016 beltpack transmitter**Features**

- 16 factory preset user-selectable UHF frequencies from 600-900MHz per 20MHz bandwidth.
- ± 40 KHz peak deviation.
- Pilotone Control.
- Very low spurious emission passed the stringent CE & FCC regulations.
- Low current consumption.
- Up to 16 hours of operation with 2 AA Alkaline batteries.
- 4-pin Min-XLR connector.
- A choice of various lavalier or Headset microphones.
- MT and GT gain controls for beltpack microphones.
- Matching battery charger: HC-30, HC-37

Specifications

Model	SM-5016
Frequency Range	UHF Band 600 - 900 MHz
Switching Bandwidth	20 MHz
Switchable Frequency	16
RF Power Output	< 35mW**
Spurious Emission	> 60 dB below carrier
Dynamic Range	> 110 dB
Display Screen	LCD
T.H.D	< 0.5%
Peak Deviation	± 40 KHz
Antenna	1/4 wave, whip antenna
Battery Type	AA x 2
Operating Life (Alkaline)	12 hours
Charging Function	YES
Battery charger	HC-30, HC-37
Connector	4-pin mini XLR type
Dimension (mm)	100x66x24
Microphone input	Lavalier or headset microphone
Weight (g)	97
Patent & Approval	CE,FCC

**** Remark:** The above specifications are subject to change without prior notice. The output power may vary from country to country.